MATERIAL SAFETY DATA SHEET

(Approved by U.S. Department of Labor as "essentially similar" to FORM OSHA-20)

SECTION I IDENTIFICATION OF PRODUCT

Manufacture's Name	Emergency Telephone No.
York Manufacturing, Inc.	207-324-1300

Address
P.O. Box 1009, Community Drive, Sanford, ME 04073

Trade Name and Synonyms
Vinyl Film - WASCOSEAL

Chemical Name and Synonyms
Flexible Vinyl Film and Sheet

Chemical Family	Molecular Formula	Mol Wt.
Plasticized PVC	N/A	N/A

SECTION II HAZARDOUS COMPONENTS OF MIXTURES

Component	%	Threshold Limit Value (units)	Components	%	Threshol Value (un
Not Applicable					

SECTION III PHYSICAL DATA

Appearance and Odor
Clear or Colored Film

Boiling Point (Degrees Fahrenheit) N/A	Melting Point (Degrees of Fahrenheit) N/A
Vapor Pressure (MM of Mercury) N/A	Specific Gravity (Water = 1) 1.2-1.8
Vapor Density (Air = 1) N/A	Percent Volatile (By Weight) N/A
Solubility in Water N/A	Evaporation Rate (Butyl Acetate = 1) < 1

SECTION IV FIRE AND EXPLOSION HAZARD DATA

Flash Point (specify method) (Degrees Fahrenheit)	Flammable Limits (Percent by Volume)	Lower	Upper
N/A		N/A	N/A

Fire Extinguishing Media
Water fog, CO_2

Special Fire-Fighting Procedures
Vinyl film will burn if exposed to flame. Use protective breathing equipment.

Unusual Fire and Explosion Hazards
Burning in an open flame may field toxic hydrogen chloride gas and metal oxides.

THIS INFORMATION IS FURNISHED WITHOUT WARRANTY, REPRESENTATION, INDUCEMENT OR LICENSE OF ANY KIND, EXCEPT THAT IT IS ACCURATE TO THE BEST OF HPG INTERNATIO KNOWLEDGE OR OBTAINED FROM SOURCES BELIEVED BY HPG INTERNATIONAL, INC. TO BE ACCURATE. HPG INTERNATIONAL DOES NOT ASSUME ANY LEGAL RESPONSIBILITY FOR USE OF I UPON SAME. CUSTOMERS ARE ENCOURAGED TO CONDUCT THEIR OWN TESTS. BEFORE USING ANY PRODUCT READ ITS LABEL.

SECTION V HEALTH HAZARD DATA

Threshold Limit Value
N/A

Effects of overexposure
Material does not pose a toxic hazard under normal use. Hazardous fumes are produced by combustion or hig tempurature decomposition.

Emergency and First Aid Procedures Inhalation: In case of exposure to fumes during hot processing, remove victim to fresh air and give CPR or oxygen if needed. Call a physician. Contact: In case of contact, flush eyes with plenty of water for 15 minutes. Flush skin with plenty of water. Call physician.

SECTION VI REACTIVITY DATA

Stability	Unstable		Conditions to Avoid
	Stable	X	Exposure to high temperatures for prolonged periods.

Incompatability (Materials to Avoid)
Strong acids, bases, solvents.

Hazardous Decomposition Products
Metal oxides, HC1, CO, CO_2

Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

SECTION VII SPILL OR LEAK PROCEDURES

Steps To Be Taken In Case Material Is Released or Spilled

Collect material and remove to disposal container. Observe all relevant federal, state and local laws.

Waste Disposal Method

Obey relevant local, state, and federal laws. Do not contaminate any lakes, streams, ponds or underground water supply.

SECTION VIII SPECIAL PROTECTION INFORMATION

Respiratory Protection (Specify Type)
Use NIOSH-approved respiratory protective equipment if exposed to flame.

Ventilation	Local Exhaust N/A	Special Ventilate in areas of hot processin
	Mechanical (General) N/A	Other

Protective Gloves	Eye Protection
N/A	Safety glasses.

Other Protective Equipment
N/A

SECTION IX SPECIAL PRECAUTIONS

Precautions To Be Taken In Handling and Storing

Protect from flame or excessive heat.

HMIS Ratings: Health - 0 Flammability - 1 Reactivity - 0

DATE	Name and Title	Sheet Number
6/94	E & RA Department	